16 Step - 4000mm

Product Overview

Step Width

500mm - Standard 850mm - Wide

Access Platform Options

Forward Access Right Access Left Access Left & Right Access

Z/STEP/16STEP



VAT Not Included Free Delivery

Options

Rubber Wheels RUGGED Wheels Swing out Rear Stabilisers Front Levelling Legs Galvanize Access Platform Rear Safety Bar Climb Prevention Bar **Bottom Gate** Basket

Mobile Steps lead time is generally 7 days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then despatch the mobile ladders on a 3 day service.

| Specification | | |
|-----------------------------|-----------------------------|-------------------------|
| Dimensions | Standard Step Width (550mm) | Wide Step Width (850mm) |
| Platform Height From Ground | 4000mm | 4000mm |
| Overall Length | 3140mm | 3140mm |
| Overall Height | 5000mm | 5000mm |
| Frame Width | 600mm | 900mm |
| Overall Axle Width | 1060mm | 1360mm |
| Platform Size | 550mm x 380mm | 850mm x 380mm |
| Step Tread Width | 550mm x 200mm | 850mm x 200mm |
| Step Tread Vertical Spacing | 250mm | 250mm |
| Weight Standard Width | 160kg | |
| Load Capacity | 300kg | 300kg |

- These mobile safety steps are fabricated in one rigid structure giving good inherent strength
- Easy to manoeuvre with 2 large 200mm nylon wheels and 2 smaller 100mm wheels housed in swivel castors.
- The mobile ladder is fitted with our industrial hi-grip step as standard, also a 100mm kick-plate and safety operating sticker.
- Our 16 step mobile step is made and supplied in 2 parts with the bolts included. This is because the mobile steps are simply too big to put on a lorry and transport.
- Mobile steps are painted as standard using a one coat primer/finish Zinfos 700CT, or can be galvanized.

