
Fixed Access Steps — Door Opening Inwards
2–3 Step

Product Overview

Z/STEP/FIXEDACCESS/IN

Capacity
Made to order



Options

2 Step / 3 Step
25mm Box / Heavy Duty 40mm Box
Galvanized
Walkway Mesh
Punched Treads
Adjustable Feet

Please call us for a lead time. These fixed access steps are built to order. Collection from our Kettering factory is possible — contact us if you wish to do this. Please contact us for delivery price.

Specifications	
Configuration	Door opening inwards
2 Step Platform Height	200–400mm
2 Step Overall Length	600mm
3 Step Platform Height	410–600mm
3 Step Overall Length	900mm
Handrail Height from Platform	+1000mm
Step Width	900mm
Step Depth	300mm
Kickplate Height	100mm
Box Section	25mm or Heavy Duty 40mm

These steps are tailored to doors opening inwards, as there is minimal platform space needed. This is because the operator doesn't need space to stand on the platform whilst the door is opening. They also come with a 100mm kickplate as standard.

Access steps are painted as standard using a one coat primer/finish - Zinfos 700CT, or can be galvanized. Available in 2 Step or 3 Step, and in 25mm box or Heavy Duty 40mm box section. Standard platform surface is chequerplate; walkway mesh and punched treads are optional.

We manufacture our access steps using prime steel and components at our factory in Kettering.

Tel: 01536 417440
Email: sales@stepsandstillages.co.uk
Website: www.stepsandstillages.co.uk

STEPS and Stillages Ltd

Brunel Close, Northfield Ave,
Kettering, NN16 9HU