Easy Slope - 1600mm

Product Overview

Z/STEP/EASY/1.6

VAT Not Included Free Delivery

Step Width

500mm - Standard 850mm - Wide

Access Platform Options

Forward Access Right Access Left Access Left & Right Access





Options

Rubber Wheels RUGGED Wheels Galvanize Access Platform Basket Rear Safety Bar Climb Prevention Bar **Bottom Gate** Swing Out Rear Stabilisers Front Levelling Legs

Mobile Steps lead time is generally 7 days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then despatch the mobile ladders on a 3 day service.

| Specification | | |
|-----------------------------|-----------------------------|-------------------------|
| Dimensions | Standard Step Width (550mm) | Wide Step Width (850mm) |
| Platform Height From Ground | 1600mm | 1600mm |
| Length | 1800mm | 1800mm |
| Overall Height | 2600mm | 2600mm |
| Frame Width | 600mm | 900mm |
| Overall Axle Width | 760mm | 1060mm |
| Platform Size | 550mm x 400mm | 850mm x 400mm |
| Step Tread Width | 550mm x 200mm | 850mm x 200mm |
| Step Tread Vertical Spacing | 200mm | 200mm |
| Weight Standard Width | 96kg | |
| Load Capacity | 300kg | 300kg |

- Our Easy Slope Range, has a slope angle of 45 degrees, and a comfortable step increment of 200mm, allowing users to descend facing forwards while carrying boxes.
- The platform height from the ground of this ladder is 1600mm.
- The mobile ladder is fitted with our industrial hi-grip step as standard, also a 100mm kick-plate and safety operating sticker.
- Mobile steps are painted as standard using a one coat primer/finish Zinfos 700CT, or can be galvanized.

