

# 8 Step -2000mm

## Product Overview

### Z/STEP/8STEP

VAT Not Included  
Free Delivery

#### Step Width

500mm - Standard  
850mm - Wide

#### Access Platform Options

Forward Access  
Right Access  
Left Access  
Left & Right Access



#### Options

Rubber Wheels  
RUGGED Wheels  
Swing out Rear Stabilisers  
Front Levelling Legs  
Galvanize  
Bottom Gate  
Rear Safety Bar  
Climb Prevention Bar  
Basket

Mobile Steps lead time is generally 7 days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then despatch the mobile ladders on a 3 day service.

| Specification               |                             |                         |
|-----------------------------|-----------------------------|-------------------------|
| Dimensions                  | Standard Step Width (550mm) | Wide Step Width (850mm) |
| Platform Height From Ground | 2000mm                      | 2000mm                  |
| Overall Length              | 1620mm                      | 1620mm                  |
| Overall Height              | 3000mm                      | 3000mm                  |
| Frame Width                 | 600mm                       | 900mm                   |
| Overall Axle Width          | 760mm                       | 1060mm                  |
| Platform Size               | 550mm x 380mm               | 850mm x 380mm           |
| Step Tread Width            | 550mm x 200mm               | 850mm x 200mm           |
| Step Tread Vertical Spacing | 250mm                       | 250mm                   |
| Weight Standard Width       | 78kg                        |                         |
| Load Capacity               | 300kg                       | 300kg                   |

- These mobile safety steps are fabricated in one rigid structure giving good inherent strength
- Easy to manoeuvre with 2 large 200mm nylon wheels and 2 smaller 100mm wheels housed in swivel castors.
- The mobile ladder is fitted with our industrial hi-grip step as standard, also a 100mm kick-plate and safety operating sticker.
- Mobile steps are painted as standard using a one coat primer/finish - Zinfos 700CT, or can be galvanized.