

# Narrow Aisle 9 Step - 2250mm

## Product Overview

Z/STEP/9STEPNARROW



VAT Not Included  
Free Delivery

### Options

Rubber Wheels  
Galvanize  
Basket

Mobile Steps lead time is generally 7 days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then despatch the mobile ladders on a 3 day service.

| Specification               |               |
|-----------------------------|---------------|
| Platform Height From Ground | 2250mm        |
| Overall Width               | 630mm         |
| Length                      | 1760mm        |
| Overall Height              | 3250mm        |
| Bottom Step Size            | 200mm x 550mm |
| Platform Size               | 400mm x 400mm |
| Step Tread Depth            | 200mm         |
| Step Tread Vertical Spacing | 250mm         |
| Weight                      | 90kg          |
| Load Capacity               | 300kg         |

- The narrow aisle mobile steps are based on our standard heavy duty range of steps - still with all the strength, but they don't have the wider rear axle
- These narrow aisle steps have the wheels mounted under the framework of the steps
- The steps are also fitted with an internal brake system as opposed to the side mounted lever to save space.
- Our standard range sports 2 fixed castors at the rear end and 2 swivel castors at the front. These swivel castors can be raised so the steps frame bottoms out on the ground
- The mobile ladder is fitted with our industrial hi-grip step as standard, also a 100mm kick-plate and safety operating sticker.
- Mobile steps are painted as standard using a one coat primer/finish - Zinfos 700CT, or can be galvanized.