
Easy Slope - 1000mm

Product Overview

Z/STEP/EASY/1.0







Step Width

500mm - Standard 850mm - Wide

Options

Rubber Wheels RUGGED Wheels Galvanize Basket Climb Prevention Bar

Mobile Steps lead time is generally 7 days. Whilst we stock the step components, the mobile steps are built to order. We would typically allow 3 days to build the steps, a day to paint them and then despatch the mobile ladders on a 3 day service.

Specification		
Dimensions	Standard Step Width (550mm)	Wide Step Width (850mm)
Platform Height From Ground	1000mm	1000mm
Length	1200mm	1200mm
Overall Height	2000mm	2000mm
Frame Width	590mm	890mm
Overall Axle Width	760mm	1060mm
Platform Size	550mm x 400mm	850mm x 400mm
Step Tread Width	550mm x 200mm	850mm x 200mm
Step Tread Vertical Spacing	200mm	200mm
Weight Standard Width	55kg	
Load Capacity	300kg	300kg

- Our Easy Slope Range, has a slope angle of 45 degrees, and a comfortable step increment of 200mm, allowing users to descend facing forwards while carrying boxes.
- The platform height from the ground of this ladder is 1000mm.
- The mobile ladder is fitted with our industrial hi-grip step as standard, also a 100mm kick-plate and safety operating sticker.
- Mobile steps are painted as standard using a one coat primer/finish Zinfos 700CT, or can be galvanized.

